

GALAXY®

line interaction
UPS

Single Phase Line Interaction UPS

Brand	GALAXY					
Model	PSN-500VA	PSN-750VA	PSN-1000VA	PSN-1500	PSN-2000	PSU-3000
Capacity	350W	525W	700W	1050W	1400W	2100W
Input						
Voltage Range		<input type="checkbox"/> 140V-275V	<input type="checkbox"/> 170V-275V	<input type="checkbox"/> 160V-300V		
Frequency				50 Hz.(±10%)		
Phase				Single		
Output						
Voltage			220Vac ± <input type="checkbox"/> 5% / <input type="checkbox"/> 8%			
Frequency			50Hz.			
Inverter Output			220 Vac			
Wave Form			Sine wave			
Battery						
Battery Voltage		12V (external battery)	24V (external battery)			48V (external battery)
Recharge Time				Less then 6 hours		
Backup Time Full Load				As per customer request		
Others						
Transfer Time				Less than 2ms		
Efficiency				Better than 90%		
Indicators	LCD/LED	LCD/LED	LCD/LED	LCD/LED	LCD/LED	LCD/LED
Relative Humidity				20 ~ 90 % (Non Condensing)		
Working Temp.				0° ~ 40° C		
Interface				RS-232		
Protection				Surge, Spike Sag, Blackout, Brownout, Flicker, Over Voltage & Under Voltage, Low & high battery charge, Over load, Output short circuit, Deep discharge & Noise (EMI & RFI) protection and Input Circuit Breaker.		



APPLICATION	SPECIAL FEATURE
Personal Computer	Advanced Technology
Workstation	Easy Maintenance & more reliability
Server	Built-in wide range voltage regulator
Medical Equipment	Anti fluctuation delay facility
Telecommunication	UPS operating software
Laboratory Equipment	User replaceable battery design
FAX / PABX / TELEX	Cold start

ISO9001:2000



Sole Agent

GALAXY ELECTRO POWER LTD.

219-220 Nawabpur Road (2nd Floor), Gausia Plaza, Dhaka-1100, Bangladesh.
Tel: 7115943, 7120406, Fax: 880-2-7112675, E-mail: galaxy@bol-online.com